



**Duro**<sup>®</sup>

Product Summary

## Ruggedized Multi-Band, Multi-Constellation Centimeter-Accurate GNSS

Swift Navigation, in partnership with Carnegie Robotics, introduces Duro—an enclosed version of the Piksi<sup>®</sup> Multi dual-frequency RTK receiver. Built for the outdoors, Duro combines centimeter-accurate positioning with military ruggedness at a breakthrough price.



### Built to Be Tough

Duro leverages design principles typically used in military hardware and results in an easy-to-deploy sensor, protected against weather, moisture, vibration, dust, water immersion and unexpected circumstances that can occur in long-term, outdoor employments.

### Easy Integration

Duro's M12 connectors are sealed and industry standard, which balances ruggedization perfectly with user-friendliness. No external sealing is required to deploy in even the harshest conditions. The exposed interfaces support varied use cases without integration headaches.

### Centimeter-Level Accuracy

Autonomous platforms require precise positioning—especially those that perform critical functions. Swift Navigation's Piksi Multi receiver within Duro utilizes real-time kinematics (RTK) technology, providing location solutions that are 100 times more accurate than traditional GNSS solutions.

### Fast Convergence Times

Multiple signal bands enable fast convergence times to high-precision mode. Single band RTK systems converge in minutes, while Piksi Multi converges to a high-precision solution within seconds. This allows for faster time to first fix (TTFF), as well as faster reacquisition times which are critical in high dynamic autonomous applications within a variety of environments.

### Leverages Piksi Multi

Multiple signal bands enable fast convergence times and multiple satellite constellations enhance availability. Piksi Multi supports GPS L1/L2, GLONASS G1/G2, BeiDou B1/B2 and Galileo E1/E5b for RTK measurements and positioning and SBAS for robust sub-meter positioning in non-RTK mode. No additional upgrade charges for constellation upgrades.

### Benefits

- Ruggedized Sensor for Long-Term Deployment
- Uses Swift Navigation's Piksi Multi
- Highly-Competitive Pricing
- Flexible Mounting Interfaces
- Future-Proof Hardware with In-Field Software Upgrades
- Intuitive LEDs for Status and Diagnostics
- Electrical Protection on all IO
- Durable and Chemical Resistant Powder-Coating
- Passive Thermal Design

### Features

- IP67 rated
- Centimeter-Level Positioning
- Dual Frequency GNSS RTK
- Raw Data Outputs from On-Board MEMS IMU

## Physical & Environmental

<b>Dimensions</b>	130 mm x 130 mm x 65 mm
<b>Weight</b>	0.8 kg (Cast Al Housing)
<b>Temperature</b>	
Operating	-40° C to +75° C
Storage	-40° C to +85° C
<b>Humidity</b>	95% non-condensing
<b>Sealing</b>	IP67
<b>Vibration</b>	
Operating and Survival (Random Vibe)	7.7 g
Operating and Survival (Sinusoidal Vibe)	5 g
<b>Mechanical Shock</b>	
Operating	40 g
Survival	75 g

## Electrical & I/O

<b>Power</b>		
Input Voltage <sup>1</sup>	10 - 35 V DC	
Typical Power Consumption <sup>2</sup>	5.0 W	
<b>Antenna LNA Power Specifications</b>		
Output Voltage	4.85 V DC	
Max Output Current	100 mA	
<b>External Connector Ports</b>		
<ul style="list-style-type: none"> <li>- 2 x RS232 Serial Ports with Optional Hardware Flow Control</li> <li>- Ethernet support up to 100Mbps</li> <li>- PPS, PV, 3 x Event Inputs</li> <li>- CANBus with Selectable Termination Resistor</li> <li>- Configurable Digital Inputs and Outputs</li> <li>- 12 V at 1A and 5 V at 250mA Power Outputs</li> </ul>		

## GNSS Characteristics

<b>GNSS Signal Tracking</b>	
GPS L1/L2, GLONASS G1/G2, BeiDou B1/B2, Galileo E1/E5b SBAS (WAAS, EGNOS, GAGAN, MSAS)	
<b>GNSS Data Rates<sup>3</sup></b>	
Measurements (Raw Data)	Up to 20 Hz
Standard Position Outputs	Up to 20 Hz
RTK Position Outputs	Up to 10 Hz
Swift Binary Protocol (SBP) and NMEA-0183	
<b>Maximum Operating Limits<sup>4</sup></b>	
Velocity	515 m/s

## Position Performance Specifications<sup>5</sup>

### Position, Velocity & Time Accuracy

Horizontal Position Accuracy (CEP 50 in SBAS Mode)	0.75 m
Velocity Accuracy	0.03 m/s RMS
Time Accuracy	60 ns RMS
Real Time Kinematic (RTK Accuracy 1σ)	
- Horizontal	0.010 m + 1 ppm
- Vertical	0.015 m + 1 ppm
RTK Initialization Parameters	
- Initialization Time	< 10 s
- Initialization Reliability	> 99%
- Solution Latency	< 30 ms

ETHERNET M12-D/F 4 POS	
1	TX +
2	RX +
3	TX -
4	RX -

POWER M12-A/M 5 POS	
1	Voltage In
2	Chassis GND
3	Power GND
4	PPS
5	Event A

SERIAL M12/A/F 8 POS	
1	Serial 0 TX
2	Serial 0 RX
3	CTS
4	EVENT C
5	GND
6	12 V Out
7	PPS Out
8	RTS

GNSS ANTENNA TNC	
Pin	Antenna
Body	Chassis

AUX M12-A/F 17 POS	
1	CAN Low
2	5V Out
3	RTS
4	CTS
5	12V Out
6	GND
7	RESERVED
8	RESERVED
9	RESERVED
10	TX
11	Rx
12	CAN High
13	PPS
14	GND
15	RESERVED
16	EVENT B
17	DO/PV



<sup>1</sup> Maximum allowed input Voltage range. Recommended Voltage input range from 12 - 24V

<sup>2</sup> Power draw without cell modem activated ~ 5W. Power draw with cell modem active ~ 6W

<sup>3</sup> Please refer the Piksi Multi product summary for additional specifics.

<sup>4</sup> As required by the U.S. Department of Commerce to comply with export licensing restrictions.

<sup>5</sup> In open sky and strong signals conditions.