

Mini Survey Antenna GPS1000

HIGH PHASE CENTER STABILITY

GPS1000 features a multi-point feeding design to achieve greater phase center stability. It effectively improves measurement accuracy and provides better positioning solutions.

TRACKING IN CHALLENGING ENVIRONMENTS

The ability to receive low elevation signals with high gain and wide beam width makes GPS1000 an excellent choice for tracking visible satellites under challenging conditions, providing the positioning solutions with precision and reliable data. It can be widely used in GNSS surveying applications where high precision is needed, such as obstructed environment of tree lines or construction.

STRONG ANTI-INTERFERENCE PERFORMANCE

The antenna LNA features an excellent out-of-band rejection performance, which can suppress the electro magnetic interference, providing the stability and reliability of GNSS signals. Also it effectively avoids disconnection dangerous when receivers are operated under complex electro magnetic environments such as communication base station applications or urban area.

DURABLE, EASY-INSTALLATION DESIGN FOR PRECISION APPLICATIONS

Its compact and lightweight design, making GPS1000 highly portable and suitable for outdoor operating in precision applications. The patented waterproof and breathable design, durable enclosure has been proven to sustain the harsh conditions by meeting IP67, easily protecting GPS1000 from dust and water for quite a long time.

KEY FEATURES

- Support GPS, GLONASS, BeiDou and Galileo signals reception
- Stable phase center guarantees the accuracy of positioning within millimeter-level
- Strong anti-interference ability to endure the challenging operating environments
- Small form factor with IP67 ruggedized structure



TECHNICAL SPECIFICATIONS

Performance

Signals Received	GPS L1/L2/L5 GLONASS L1/L2/L3 BeiDou B1/B2/ B3 Galileo E1/E6/E5a/E5b
Nominal Impedance	50 ohm
Polarization	RHCP
Axial Ratio	≤ 3 dB
Gain at Zenith	(90°)
1164-1300MHz	5.5 dBi (maximum)
1520-1615MHz	5.5 dBi (maximum)
LNA Gain	40 dB (typical)
Noise Figure	≤ 2.0 dB
Output VSWR	≤ 2.0
Operation Voltage	3.3 ~ 12V DC
Operation Current	≤ 45 mA
Group Delay Ripple	≤ 5 ns

Mechanical Specification

Dimension	φ 152*62.2 mm
Connector	TNC Female
Weight	410 g
Mounting	BSW5/8"-11screw, 12-14mm

Environment Specification

Storage Temp	-55 °C to +85° C
Operating Temp	-40° C to +85° C
Humidity	95% No-condensing
Water/Dust Resistance	IP67