# sbp2report User's Guide

# Overview

This document describes usage of the sbp2report v2.3.1 Swift Binary Protocol (SBP) log converter tool.

### sbp2report Introduction

The sbp2report software tool, available for Windows, Linux and macOS computers, converts SBP binary and SBP JSON log files to a set of human-friendly files for easy field test data review. The sbp2report generates following output files for each SBP log file:

filename.csv	- Navigation data in CSV format (time, status, lat, lon, alt, etc.)
filename-trk.csv	- Satellite tracking data in CSV format (time, each SV signal level)
filename-ins.csv	- Inertial sensors (accelerometer, gyro, magnetometer) raw data in CSV format
filename-msg.csv	- All messages (partially decoded) in CSV format
filename.kml	- Traveled trajectory in Google Earth format
filename-alt.plt	- Altitude graph in gnuplot format
filename-bsln.plt	- RTK baseline length graph in gnuplot format
filename-bsln-trj.plt	- RTK baseline trajectory graph in gnuplot format
filename-corr-age.plt	- Corrections age graph in gnuplot format
filename-spd.plt	- Speed graph in gnuplot format
filename-svs.plt	- Satellites used in solution graph in gnuplot format
filename-trj.plt	- Traveled trajectory graph in gnuplot format
filename-trk.plt	- Tracked satellites graph in gnuplot format
filename-trk-xxx.plt	- Tracked satellites signal levels in gnuplot format. One file per GNSS constellation.
filename-stats.txt	- General statistic information

The sbp2report can be downloaded from <u>support.swiftnav.com</u> (section Downloads -> Tools). Installation instructions and release notice are included there as well.

A following third-party software tools are recommended to view files created by the sbp2report:

KML	- Google Earth ( <u>https://www.google.com/earth/desktop/</u> )
CSV	<ul> <li>Microsoft Excel or other spreadsheet program</li> </ul>
PLT	- gnuplot ( <u>http://www.gnuplot.info/</u> ). See Appendix A for installation details.
ТХТ	- Any text file viewer/editor



### sbp2report Usage

The sbp2report is a command line tool. Command Prompt / Terminal window is required to run the program. Start the tool with no parameters to display usage help. The tool can process multiple input files at once. Expected file extensions are .sbp for binary file and .sbp.json for SBP JSON file. Output files are saved in the current working directory.

Tool options:

-r rate	<ul> <li>Overrides expected solution data rate settings [Hz]. Default is 10.0 Hz.</li> </ul>
-kr rate	- KML file output data rate [Hz]. Can be 1, 2, 5 or 10. Smaller file loads quicker.
-b	- Displays base station position in KML file.
-hm	- Heading mode - changes PLT output files to show heading status instead of position.
-ho offset	- Heading offset [deg]. Default 0. Range: -180 to 180 deg.
-tow begin end	- Limits TOW range [begin,end) for output [s]. Output files are saved in sub-directory.
-t title	- Title for the stats and plot output files. Max 20 chars.
-gicons	- Use original Google icons in KML.

#### Usage examples:

```
sbp2reportswift-gnss-20190506-142841.sbp.jsonEnter>- converts all files with default extension from current directory;sbp2report-kr 1 * <Enter>- converts all files with default extension from current directory;KML data is decimated to 1 Hz- converts all files with default extension from currentsbp2report-tow 595925 595940 * <Enter>- converts all files with default extension from current
```

directory; output duration is limited to TOW range specified

sbp2report \\* <Enter> - wildcard usage on Linux or macOS system

**Note:** it is recommended to launch the tool from a directory where log files are saved.

Example: if logs are in c:\logs\2019-06-05 directory process data in two steps:

c:\> cd \logs\2019-06-05 **<Enter>** 

c:\logs\2019-06-05> sbp2report (options and log name) <Enter>

Position and heading mode encoding (CSV files):

- 0 No Fix
- 1 SPS
- 2 DGPS
- 3 Float RTK
- 4 Fixed RTK
- 5 DR (Dead Reckoning)
- 6 SBAS

Position and heading mode color encoding (KML and gnuplot files):

Red	- SPS
Cyan	- DGPS
Blue	- Float RTK
Green	- Fixed RTK

- Black DR
- Purple SBAS



### sbp2report Output Examples

Pictures below present a few sample outputs generated by the sbp2report.

#### General File Statistic (text file)

Lister - [c:\LOGS\2019-06-11-drive2-sf-280-85-sj\pm1\swift-gnss-20190611-225053-stats.txt]	
<u>Eile Edit Options Encoding H</u> elp	50 <u>%</u>
はNSS Statistic Report File Name: swift-gnss-20190611-225053.sbp.json SBP Data Length: 47999005 B (45.78 MB) Valid: 47999005 B (45.78 MB) Invalid: 0 B Errors Count: 0 Errors Rate: 0.000 %	
Average Data Rate: 8726.9 B/s (8.5 KB/s)	
Receiver Name:Piksi MultiProduct ID:Piksi MultiSerial Number:00108072917000219Firmware Version:v2.3.17Firmware Date:2019-06-11 19:08:02 UTCFirmware ID:v2.3.17Solution Frequency:10.0 HzHeading Offset:0.0 deg	
GPS TOW: Start: 255071.400 s End: 260571.500 s	
Duration: 5500.100 s (1h 31m 40.1s) Distance Traveled: 99917.3 m (99.9 km, 62.1 mi)	
Messages Count: Position: 54989 (99.98%) Speed: 54134 (98.42%) Heading: 0 (0.00%)	
Position Mode: All Fixes: 54169 (98.49%) RTK Fixes: 54067 (98.30%) No fix: 833 (1.51%) SPS: 21 (0.04%) SBAS: 55 (0.10%) DGPS: 26 (0.05%) RTK Float: 6396 (11.63%) RTK Fixed: 47671 (86.67%) DR: 0 (0.00%)	
Satellites Tracked: GPS GLONASS Galileo BeiDou All L1 L2 G1 G2 E1 E2 B1 B2 Min: 11 3 0 0 0 1 1 5 1	SBAS L1 0
Max: 34 10 6 8 8 8 8 8 3 Avg: 27.0 7.7 5.4 3.9 3.0 6.7 6.8 7.6 2.7	1 1.0
Satellites in Use: All Min: 5 Max: 15 Avg: 14.3	
•	ب. ان ا



#### Trajectory (Google Earth)



#### Hints:

- Click on position icon to display detailed information
- Position icons, Track lines and base station position can be individually enabled/disabled
- Use data decimation option (-kr X) for larger (over 1 hour) logs

Base station position indicator:





#### Vehicle Speed (gnuplot)



#### Hints:

- Enable gnuplot option "Don't quit until all windows are closed (persist)" to keep graph on the screen
- Mouse roller scrolls graph up/down
- Shift key + mouse roller scrolls graph left/right
- Ctrl key + mouse roller zooms graph in/out
- Q key quits gnuplot



#### **Navigation Data (Excel)**

	A	В	С	D	E	F	G	н	I	J	ĸ	L	М	N
1	GPS Week	GPS TOW [s]	Pos Mode	INS Mode	Hdg Mode	SVs Tracked	SVs Used	UTC Date	UTC Time	Lat [deg]	Lon [deg]	Alt Ellips [m]	SOG [m/s]	COG [deg]
2	2010	322312.4	4	0		24	15	7/18/2018	17:31:34.4	37.77118501	-122.4030965	-6.96	0.01	59.04
3	2010	322312.5	4	0			15	7/18/2018	17:31:34.5	37.77118502	-122.4030966	-6.95	0.04	270
4	2010	322312.6	4	0			15	7/18/2018	17:31:34.6	37.77118502	-122.4030965	-6.96	0.03	80.54
5	2010	322312.7	4	0			15	7/18/2018	17:31:34.7	37.77118502	-122.4030965	-6.95	0.05	116.57
6	2010	322312.8	4	0			15	7/18/2018	17:31:34.8	37.77118502	-122.4030966	-6.95	0.04	213.69
7	2010	322312.9	4	0		17	15	7/18/2018	17:31:34.9	37.77118501	-122.4030966	-6.95	0.01	194.04
8	2010	322313	4	0			15	7/18/2018	17:31:35.0	37.77118501	-122.4030966	-6.95	0.01	51.34
9	2010	322313.1	4	0-									153.43	
10	2010	322313.2	4			Pos Mode p1							329.04	
11	2010	322313.3	4	4.5	;								02	201.8
12	2010	322313.4	4	1	+ <u> </u>								01	341.57
13	2010	322313.5	4	3.5									01	<b>Y</b> 149.04
14	2010	322313.6	4		3				┛╹				01	276.34
15	2010	322313.7	4	21									01	216.87
16	2010	322313.8	4	0	,								00	198.43
17	2010	322313.9	4										02	63.43
18	2010	322314	4	1.:	)								03	116.57
19	2010	322314.1	4										02	318.01
20	2010	322314.2	4	0.5									01	180
21	2010	322314.3	4	(	)								01	299.74
22	2010	322314.4	4		110 219 328	437 546 655 875 875	10911200 1200 1309	1527 1636 1745 1745 1854 1963	21812218122290 223990 223990 22508	2726 2728 2835 2835 2944 2053 3053 3053 3053	3380 3388 3489 3598 3598 3707 3816 3816	4034 4145 4255 4255 4361 4361 4361 4470	16/16 D2	114.78
23	2010	322314.5	4	0-			13	1/ 10/ 2010	170.30.3	57.77110502	122.4030300		-02	245.56
24	2010	322314.6	4	0			15	7/18/2018	17:31:36.6	37.77118502	-122.4030966	-6.95	0.02	234.46
25	2010	322314.7	4	0			15	7/18/2018	17:31:36.7	37.77118503	-122.4030966	-6.95	0.03	47.12
26	2010	322314.8	4	0			15	7/18/2018	17:31:36.8	37.77118502	-122.4030966	-6.95	0.02	150.26

#### Notes:

- Empty cells indicate invalid or not available data
- Last three columns (Delta TOW, 2D Delta Position and 2D Delta Position) are computed by the tool. All other data come directly from SBP messages.
- The Delta TOW, 2D Delta Pos and 3D Delta Pos compute delta from a previous data set.

#### Acronyms used in CSV file headers

- TOW Time Of the Week
- Pos Position
- INS Inertial
- Hdg Heading
- SV Satellite Vehicle
- UTC Universal Time Coordinated
- Lat Latitude
- Lon Longitude
- Alt Altitude
- Ellips Ellipsoid
- SOG Speed Over Ground
- COG Course Over Ground
- Vert Vertical
- Vel Velocity
- PDOP Position Dilution Of Precision
- HDOP Horizontal Dilution Of Precision
- EHPE Estimated Horizontal Position Error
- EVPE Estimated Vertical Position Error

- 2D Two-dimensional (horizontal)
- 3D Three-dimensional
- Corr Corrections
- IMU Inertial Measurement Unit
- Temp Temperature
- Acc Accelerometer
- Gyr Gyroscope
- Mag Magnetometer
- GPS Global Positioning System
- GLO GLONASS
- GAL Galileo
- BDS BeiDou



# Appendix A - gnuplot Installation Details

The easiest and recommended way to display PLT files with gnuplot is to associate .plt file extension with gnuplot program and then double-click on a file . On MacOS association needs to be done to the gnuplot-launch program.

It is recommended to install gnuplot with wxt (wxWidgets) terminal for interactive plot control.

Below are detailed gnuplot installation instructions for Windows, Linux and MacOS.

#### Windows

- 1. Program installer can be downloaded from <a href="http://gnuplot.info/download.html">http://gnuplot.info/download.html</a>
- 2. During installation enable file association for .plt files and enable "Add application directory to the PATH environment variable".
- 3. After first start enable gnuplot option "Don't quit until all windows are closed (persist)" to keep graph on the screen.

#### Linux

- 1. Install gnuplot using command sudo apt-get install gnuplot-qt or sudo apt-get install gnuplot-x11
- 2. In the file viewer right-click on any .plt file and in Open With option select gnuplot

Note: The terminal type needs to be updated manually in the .plt file.

#### MacOS

- 1. Install gnuplot using command: brew install gnuplot --with-wxmac
- 2. Copy gnuplot-install app to the Applications folder
- 3. In Finder control-click (right-click) on any .plt file generated by sbp2report and click Get Info. In Open With section click Other and enable All Applications view. Then select gnuplot-launch as application and check Always Open With checkbox.

Note: The -trk.plt files do not open correctly at this time.

