


CIGARETTE LIGHTER PLUG W/3A FUSE

NOTES:

1. PIN ASSIGNMENT SEE TO WIRE LIST.
2. ELECTRICAL TEST CONDITION:
 - (a) 100%OPEN, SHORT & MISWIRE TEST,
 - (b) INSULATOR RESISTANCE:5Mohm MIN.
DC 300V 0.01sec.
 - (c) CONTACT RESISTANCE:5ohm MAX.
3. RoHS COMPLIANCE.



Swift PN 00266-01 rev 01

3	1A750434	Conn.	Cigarette Lighter Plug w/3A Fuse
2	1A750230	Conn.	DC-P-R2E ϕ 5.5mm* ϕ 2.1mm Black Insulator
1		Cable	2C*20AWG UL2464 OD 4.50mm Black PVC Jacket
No	Part No	Title	Description

UNLESS OTHERWISE SPECIFIED TOLERANCE		ARCHTECH ELECTRONICS CORP.
ANG.	±	
0.	±	
.00	±	
SCALE: NONE	UNIT: mm	CUSTOMER P/N.: 90-00266-01
DRAWN:	10/08/'16	DRAWN NAME:
CHECKED:	/ /	CIGARETTE PLUG/DC-P ROUND CORD AL=1500mm
APPROVED:	/ /	PRODUCT NO: AA853805
SIZE A4		FILE NAME: TDC-00266
REV. X1		

	Increase length to 1.5M		11/02/'16
REV.	DESCRIPTION	DATE	REV.
1			
2			
3			
4			
5			
6			
7			
8			
9			
10			