



PIN ASSIGNMENT

P1		P2
1	BLACK	CENTER
3	WHITE	SHELL

- NOTES:
- PIN ASSIGNMENT SEE TO WIRE LIST.
 - ELECTRICAL TEST CONDITION:
 - 100%OPEN, SHORT & MISWIRE TEST,
 - INSULATOR RESISTANCE:5Mohm MIN.
DC 300V 0.01sec.
 - CONTACT RESISTANCE:5ohm MAX.
 - RoHS COMPLIANCE.

Swift PN 00348-01 rev 02

4	G0001	Mold	ALL CONNECTORS OVERMOLD BLACK PVC
3	A0008	Conn	DC JACK 5.5mm*2.1mm NICKEL PLATING
2	A0568	Conn	M12 5P A-CODE FEMALE BLACK INSULATOR SOLDER TYPE
1	E0737	Cable	#18AWG/2C UL2464 OD:6.0mm BLACK PVC
No	Part No	Title	Description

UNLESS OTHERWISE SPECIFIED TOLERANCE		ARCHTECH ELECTRONICS CORP.
ANG.	±	
0.	±	
.0	±	
.00	±	
SCALE:	NONE	UNIT: mm
DRAWN:		CUSTOMER P/N.: 90-M12A5F/DCJ-08
CHECKED:		DRAWN NAME:
APPROVED:		M12 A-CODE 5P FEMALE/DC-JACK POWER CABLE AL=2.5M
		PRODUCT NO: AA8552622
		FILE NAME: 90-M12A5F/DCJ-08

△		△	
△		△	
△		△	
REV.	DESCRIPTION	DATE	REV.
1			4
			5
			6
			7
			8
			9
			10